


ECONOMICAL PRESSURE SWITCH Vacuum and Compound Ranges Available, Adjustable Set Point





The **Series A1PS/A1VS Economical Pressure Switch** is designed with a 15 Amp SPDT switch for direct control of pumps and motors. Available in pressure, vacuum, or compound ranges, the switches offer a field adjustable set point. Easily adjust the switch by aligning the top of the self locking adjusting nut with the desired setting indicated on the adjacent range scale. Connection is 1/4" male NPT for quick installation and can be mounted in any position.

BENEFITS/FEATURES

- 15 A contact allows direct control reducing costs and reliability by having to introduce additional contacts and relays

 Field adjustable reduces installation time bring application on-line faster

APPLICATIONS • OEM

- Compressors
- Process equipment
- Motor control

SPECIFICATIONS

Service: Compatible liquids or gases.
Wetted Materials: Diaphragm: Buna-N; Body with fitting: Zinc alloy, chromate

Temperature Limits: -31 to 185°F (-35 to 85°C).

Pressure Limits: 600 psig.

Vacuum Limits: 29.9" Hg (vacuum and compound models only).

Switch Type: SPDT snap action.

Electrical Ratings: 15 A (resistive) @ 250 VAC, 1/2 HP @ 250 VAC.

Electrical Connections: Three screw terminals.

Process Connection: 1/4" male NPT.

Set Point: Field adjustable via knurled screw cap.

Cycling: Not to exceed 1 Hz. Sensor Element: Diaphragm. Weight: 7.4 oz (209 g).

weignt.	7.4 02 (208	g).
Agency	Approvals:	UI
, .g ,	, .pp. 0 . a.o.	<u> </u>

• Pump control									
MODEL CHART									
	Set Point Range, (kPa)	Repeatability, (kPa)	Deadband (approx.), (kPa)	Model	Set Point Range, (kPa)	Repeatability, (kPa)	Deadband (approx.), (kPa)		
A1PS-24 A1PS-34	1.5 to 3.5 psi (10 to 24) 3 to 40 psi (21 to 276) 30 to 150 psi (207 to 1034) 100 to 500 psi (689 to 3445)				6-28" Hg (-20 to -94) 28" Hg to 3.5 psig (-94 to 24)	±1.2" Hg (-4) ±1.2" Hg (-4), ±0.15 psi (1)	3-14" Hg (-10 to -47) 6" Hg - 1.5 psi (-20 to 10)		